

Micah Swartz, P.E.	Project Number:	MS24-12008
	Project Name:	Premium Vinyl V-4500 - XX
	Date:	9/8/2025

**Product Approval Supporting Calculations
Alternative Anchorage Analysis & Design
R1 - Admin Update**

Project Number: MS24-12008


Drawing Number: D014758

Reference Test Report: NCTL-210-4150-02

Product Name: V-4500 Sliding Vinyl Door 71.75" x 79.8125"

Prepared for:

Jeld-Wen Windows & Doors
3737 Lakeport Blvd.
Klamath Falls, OR



Prepared by:
Micah Swartz, P.E.

A handwritten signature in blue ink, appearing to read "Micah Swartz", written over a horizontal line.

Micah Swartz, PE
Florida License No. PE 93573

09/11/25

This item has been digitally signed and sealed by Micah Swartz, P.E. on the date adjacent to the seal.

Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

Micah Swartz, P.E.	Project Number:	MS24-12008
	Project Name:	Premium Vinyl V-4500 - XX
	Date:	9/8/2025
	Page:	2 of 13

Scope:

Micah Swartz, P.E. is contracted by Jeld-Wen Windows & Doors to evaluate alternative anchorage for the product: V-4500 Sliding Vinyl Door 71.75" x 79.8125". This evaluation is based on testing performed by National Certified Testing Laboratories in Orlando, FL, test report no.: NCTL-210-4150-02 and dated 07/09/19.

This evaluation does not include the air infiltration, water resistance or water penetration of the installation method or the installed product. In addition, the design of the building substrate to resist the superimposed loads is by others.

Reference Standards:

Current edition of the Florida Building Code, Building

ANSI/AWC NDS - National Design Specification (NDS) for Wood Construction

AISI S100 North American Specification for the Design of Cold-Formed Steel Structural Members

ICC-ES Report ESR-1976 ITW Buildex TEKS Self-Drilling Fasteners

ICC-ES Report ESR-2196 Hilti Self Drilling Screws to connect cold-formed steel

NOA 24-0102.06 Tapcon Concrete and Masonry Anchors with Advanced Threadform Technology

Certification of Independence:

In accordance with Rule 61G20-3 Florida Administrative Code, Micah Swartz, P.E. hereby certifies the following:

(1) Micah Swartz, P.E. does not have, nor does it intend to acquire or will it acquire, a financial interest in any company manufacturing or distributing products tested or labeled by the agency.

(2) Micah Swartz, P.E. is not owned, operated or controlled by any company manufacturing or distributing products it tests or labels.

(3) Micah Swartz, P.E. does not have, nor will acquire, a financial interest in any company manufacturing or distributing products for which the reports are being issued.

(4) Micah Swartz, P.E. does not have, nor will acquire, a financial interest in any other entity involved in the approval process of the product.

Micah Swartz, P.E.	Project Number:	MS24-12008
	Project Name:	Premium Vinyl V-4500 - XX
	Date:	9/8/2025
	Page:	3 of 13

Design Summary:

The table below summarizes the product: V-4500 Sliding Vinyl Door 71.75" x 79.8125" and their corresponding performance levels as established by testing.

Table 1: Summary of Test Results

Series/Model	Test Report Number	Size (W x H)	Performance
V-4500 Sliding Vinyl Door 71.75" x 79.8125"	NCTL-210-4150-02 (07/09/19)	71.75" x 79.8125"	+65 psf / -70 psf

As Tested Design:

Screw Information:

Screw Size: 10 Screw Embed: 1.5 in Edge Distance: 3/4 in (minimum)

Wood Screw Lateral: 149 lbs

Alternative Fasteners:

Screw Information:

Screw Size: 10 Screw Embed: 1.5 in Edge Distance: 3/4 in (minimum)

Wood Screw Withdrawal: 228 lbs

Wood Screw Lateral: 149 lbs

TEK Screw Information:

Screw Size: 10-16

TEK Withdrawal: 145 lbs

TEK Lateral: 147 lbs

Tapcon Information:

Tapcon Size: 1/4 Embedment: 1-1/4 in (minimum) Edge Distance: 2-1/2 in (minimum)

Tapcon Lateral (Concrete): 203 lbs

Tapcon Lateral (CMU): 161 lbs

Micah Swartz, P.E.	Project Number:	MS24-12008
	Project Name:	Premium Vinyl V-4500 - XX
	Date:	9/8/2025
	Page:	4 of 13

Summary of Test Results - Plastics Checklist

Table 2: Summary of Test Results - Plastics Checklist

Product	Test Report Number	Test Standard	Performance
SMC Skin (fiberglass material)	ESP010982P	ASTM D638 (before and after G155)	-2.2% (averaged)
		ASTM D1929	770 °F (410 °C)
		ASTM D2843	62
		ASTM D635	Classification HB

The testing summarized in the table above was conducted by Element Materials Technology in St Paul, MN on 02/26/13 and meets the requirements listed in Miami-Dade County Checklist #0445, For the approval of: Plastic and Foam Plastic.

Micah Swartz, P.E.	Project Number: MS24-12008
	Project Name: Premium Vinyl V-4500 - XX
	Date: 9/8/2025 Page: 5 of 13

Subject: As Tested - Wood Screw Lateral Design - Single Shear

Input:
 Calculation:

Screw Information:

Screw Size: 10
 Screw Embed: 1.5 in

Root Diameter: 0.152 in

Main Member Type: S-P-F G: 0.42 F_{em}: 3,350 psi thickness (t_m): 1.5 in

Side Member Type: PVC G: N/A F_{es}: 13,750 psi thickness (t_s): 0.125 in

Lateral Design Factors - Table 12.3.1A (NDS)

D:	0.152	in	Diameter
F _{yb} :	90	ksi	Dowel Bending Yield Strength
F _{em} :	3,350	psi	Main Member dowel bearing strength
F _{es} :	13,750	psi	Side Member dowel bearing strength
l _m :	1.5	in	Main Member dowel bearing length
l _s :	0.125	in	Side Member dowel bearing length
R _d :	2.2		Reduction term - Table 12.3.1B (NDS)
R _e :	0.2436		= F _{em} /F _{es}
R _t :	12.0		= l _m /l _s
k ₁ :	1.135		See Table
k ₂ :	0.662		See Table

Reference Lateral Design Values - Table 12.3.1A (NDS)

Z_{I_m}: 347 lbs

$$Z_{I_m} = \frac{D l_m F_{em}}{R_d} \text{ (EQ 12.3 - 1)}$$

Z_{II}: 135 lbs

$$Z_{II} = \frac{k_1 D l_s F_{es}}{R_d} \text{ (EQ 12.3 - 3)}$$

Z_{III_m}: 154 lbs

$$Z_{III_m} = \frac{k_2 D l_m F_{em}}{(1 + 2R_e) R_d} \text{ (EQ 12.3 - 4)}$$

Z_{IV}: 134 lbs

$$Z_{IV} = \frac{D^2}{R_d} \sqrt{\frac{2 F_{em} F_{yb}}{3(1 + R_e)}} \text{ (EQ 12.3 - 6)}$$

Z_{MIN}: 134 lbs

Note: Side member is part of the Jeld-Wen assembly and verified during testing. Modes Z_{I_s} and Z_{III_s} are not applicable to the calculation.

Micah Swartz, P.E.	Project Number:	MS24-12008
	Project Name:	Premium Vinyl V-4500 - XX
	Date:	9/8/2025
	Page:	6 of 13

Subject: As Tested - Wood Screw Lateral Design - Single Shear Cont.

Adjusted Lateral Design Values

$$Z' = Z * C_D * C_M * C_t * C_g * C_{\Delta} - \text{As per table 11.3.1 NDS}$$

C _D :	1.6	Load Duration Factor - Table 2.3.2 (NDS)
C _M :	1.0	Wet Service Factor - Table 11.3.3 (NDS)
C _t :	1.0	Temperature Factor - Table 11.3.4 (NDS)
C _g :	1.0	Group Action Factor - Section 11.3.6 (NDS)
C _Δ :	1.0	Geometry Factor - Section 12.5.1.1 (NDS)

$$Z': \boxed{214} \text{ lbs}$$

Fastener Bending Across Shim Space

Ω:	1.67	
L:	0.25	in Maximum Shim Gap
D:	0.152	in Diameter
F _{yb} :	90	ksi Dowel Bending Yield Strength

$$\frac{F_{yb}}{\Omega} = \frac{M}{S} = \frac{16ZL}{\pi D^3} \Leftrightarrow Z = \frac{F_{yb} \pi D^3}{16 \Omega L}$$

$$\text{Where } M = \frac{ZL}{2} \text{ (Guided Bending)}$$

$$Z_n/\Omega: \boxed{149} \text{ lbs}$$

Bearing on Masonry Strap

Ω:	3.00	
F _u :	33	ksi Tensile Strength of strap
t:	20	GA
t:	0.036	in thickness of strap
D:	0.152	in

$$\frac{P_{nv}}{\Omega} = 2.7 * t * D * F_u - (EQ.J4.3.1 - 4, AISI S100)$$

$$P_{nv}/\Omega: \boxed{162} \text{ lbs}$$

Micah Swartz, P.E.	Project Number:	MS24-12008
	Project Name:	Premium Vinyl V-4500 - XX
	Date:	9/8/2025

Subject:	Wood Screw Withdrawal	Input:	
		Calculation:	

Screw Information:						
Screw Size:	10	Root Diameter:	0.152	in		
Screw Embed:	1.5	in				
Main Member Type:	S-P-F	G:	0.42	F _{em} :	3,350	psi

$W' = W * C_D * C_M^2 * C_t$ – As per table 11.3.1 NDS

C _D :	1.6	Load Duration Factor - Table 2.3.2 (NDS)
C _M :	1.0	Wet Service Factor - Table 11.3.3 (NDS)
C _t :	1.0	Temperature Factor - Table 11.3.4 (NDS)

W:	95	lbs/in - Table 12.2B (NDS)
W:	143	lbs

W':	228	lbs
-----	-----	-----

Micah Swartz, P.E.	Project Number:	MS24-12008
	Project Name:	Premium Vinyl V-4500 - XX
	Date:	9/8/2025
		Page: 8 of 13

Subject: Wood Screw Lateral Design - Single Shear

Input:
 Calculation:

Screw Information:

Screw Size: 10
 Screw Embed: 1.5 in

Root Diameter: 0.152 in

Main Member Type: S-P-F

G: 0.42

F_{em}: 3,350 psi

thickness (t_m): 1.5 in

Side Member Type: PVC

G: N/A

F_{es}: 13,750 psi

thickness (t_s): 0.125 in

Lateral Design Factors - Table 12.3.1A (NDS)

D:	0.152	in	Diameter
F _{yb} :	90	ksi	Dowel Bending Yield Strength
F _{em} :	3,350	psi	Main Member dowel bearing strength
F _{es} :	13,750	psi	Side Member dowel bearing strength
l _m :	1.5	in	Main Member dowel bearing length
l _s :	0.125	in	Side Member dowel bearing length
R _d :	2.2		Reduction term - Table 12.3.1B (NDS)
R _e :	0.2436		= F _{em} /F _{es}
R _t :	12.0		= l _m /l _s
k ₁ :	1.135		See Table
k ₂ :	0.662		See Table

Reference Lateral Design Values - Table 12.3.1A (NDS)

Z_{I_m}: 347 lbs

$$Z_{I_m} = \frac{D l_m F_{em}}{R_d} \text{ (EQ 12.3 - 1)}$$

Z_{II}: 135 lbs

$$Z_{II} = \frac{k_1 D l_s F_{es}}{R_d} \text{ (EQ 12.3 - 3)}$$

Z_{III_m}: 154 lbs

$$Z_{III_m} = \frac{k_2 D l_m F_{em}}{(1 + 2R_e) R_d} \text{ (EQ 12.3 - 4)}$$

Z_{IV}: 134 lbs

$$Z_{IV} = \frac{D^2}{R_d} \sqrt{\frac{2 F_{em} F_{yb}}{3(1 + R_e)}} \text{ (EQ 12.3 - 6)}$$

Z_{MIN}: 134 lbs

Note: Side member is part of the Jeld-Wen assembly and verified during testing. Modes Z_{I_s} and Z_{III_s} are not applicable to the calculation.

Micah Swartz, P.E.	Project Number:	MS24-12008
	Project Name:	Premium Vinyl V-4500 - XX
	Date:	9/8/2025
	Page:	9 of 13

Subject: Wood Screw Lateral Design - Single Shear Cont.

Adjusted Lateral Design Values

$$Z' = Z * C_D * C_M * C_t * C_g * C_{\Delta} - \text{As per table 11.3.1 NDS}$$

C _D :	1.6	Load Duration Factor - Table 2.3.2 (NDS)
C _M :	1.0	Wet Service Factor - Table 11.3.3 (NDS)
C _t :	1.0	Temperature Factor - Table 11.3.4 (NDS)
C _g :	1.0	Group Action Factor - Section 11.3.6 (NDS)
C _Δ :	1.0	Geometry Factor - Section 12.5.1.1 (NDS)

$$Z': \quad 214 \text{ lbs}$$

Fastener Bending Across Shim Space

Ω:	1.67	
L:	0.25	in Maximum Shim Gap
D:	0.152	in Diameter
F _{yb} :	90	ksi Dowel Bending Yield Strength

$$\frac{F_{yb}}{\Omega} = \frac{M}{S} = \frac{16ZL}{\pi D^3} \Leftrightarrow Z = \frac{F_{yb} \pi D^3}{16 \Omega L} \quad \text{Where } M = \frac{ZL}{2} \text{ (Guided Bending)}$$

$$Z_n/\Omega: \quad 149 \text{ lbs}$$

Bearing on Masonry Strap

Ω:	3.00	
F _u :	33	ksi Tensile Strength of strap
t:	20	GA
t:	0.036	in thickness of strap
D:	0.152	in

$$\frac{P_{nv}}{\Omega} = 2.7 * t * D * F_u - (EQ.J4.3.1 - 4, AISI S100)$$

$$P_{nv}/\Omega: \quad 162 \text{ lbs}$$

Micah Swartz, P.E.	Project Number:	MS24-12008
	Project Name:	Premium Vinyl V-4500 - XX
	Date:	9/8/2025
	Page:	10 of 13

Subject:

Input:
Calculation:

Shear Strength of Fastener - ESR 1976

Screw Size:

P_{nv}/Ω : lbs See ESR 2196

Tensile Pullout - ESR 1976

Screw Size:

F_u : ksi Tensile Strength of material NOT in contact with screw head

t: GA

t: in Thickness of material NOT in contact with screw head

P_{nv}/Ω : lbs See ESR 2196

Tensile Pullover

Note: The tensile pullover analysis checks the material IN contact with the screw head. This material is part of the Jeld-Wen assembly and has been verified by testing. Below is a check to ensure the head size of the TEK screw is equal to or larger than the head of the tested fastener, ensuring compliance.

Tested Fastener Head Size:

Screw Size: Tested fastener is a

Head Size: in

TEK Screw Head Size:

Screw Size:

Head Size: in

Micah Swartz, P.E.	Project Number:	MS24-12008
	Project Name:	Premium Vinyl V-4500 - XX
	Date:	9/8/2025
		Page: 11 of 13

Subject: TEK Lateral Design

Input:

Calculation:

Shear Strength of Fastener - ESR 1976

Screw Size:

P_{nv}/Ω : lbs See ESR 2196

Bearing Strength of Material NOT in Contact with Screw Head - AISI S100

Screw Size: Ω :

D: in Root Diameter of TEK Screw

F_u : ksi Tensile Strength of material NOT in contact with screw head

t: GA

t: in Thickness of material NOT in contact with screw head

$$\frac{P_{nv1}}{\Omega} = 2.7 * t * D * F_u - (EQ.J4.3.1 - 3, AISI S100)$$

$$\frac{P_{nv2}}{\Omega} = 4.2 \sqrt{t^3 * D} * F_u - (EQ.J4.3.1 - 1, AISI S100)$$

P_{nv1}/Ω : lbs

P_{nv2}/Ω : lbs

P_{nv}/Ω : lbs $\frac{P_{nv}}{\Omega} = \text{smallest of } \frac{P_{nv1}}{\Omega} \text{ and } \frac{P_{nv2}}{\Omega}$

Bearing Strength of Material IN in Contact with Screw Head

Note: Material IN contact with the screw head is part of the Jeld-Wen assembly and has been verified by testing.

Fastener Bending Across Shim Space

L: in Maximum Shim Gap Ω :

D: in Root Diameter of TEK Screw

F_{yb} : ksi Yield Strength of TEK Screw

$$\frac{F_{yb}}{\Omega} = \frac{M}{S} = \frac{16P_n L}{\pi D^3} \Leftrightarrow P_n = \frac{F_{yb} \pi D^3}{16 \Omega L}$$

Where $M = \frac{P_n L}{2}$ (Guided Bending)

P_n/Ω : lbs

Micah Swartz, P.E.	Project Number:	MS24-12008
	Project Name:	Premium Vinyl V-4500 - XX
	Date:	9/8/2025
	Page:	12 of 13

Bearing Strength of Masonry Straps - AISI S100

Screw Size:	10-16	TEK Screw	Ω:	3.00
D:	0.138	in	Root Diameter of TEK Screw	
F _u :	33	ksi	Tensile Strength of Masonry Strap	
t:	20	GA		
t:	0.0359	in	Thickness of Masonry Strap	

$$\frac{P_{nv}}{\Omega} = 2.7 * t * D * F_u - (EQ.J4.3.1 - 3, AISI S100)$$

P_{nv}/Ω: 147 lbs

Micah Swartz, P.E.

Project Number: MS24-12008

Project Name: Premium Vinyl V-4500 - XX

Date: 9/8/2025

Page: 13 of 13

Subject: Tapcon Lateral Design

Input:

Calculation:

Tapcon Size:

Size: 1/4

D: 0.25 in Nominal Diameter

D_{sh}: 0.19 in Shank Diameter**Fastener Shear Capacity - 3,000 psi Concrete**P_{nv}/Ω: 237 lbs See Table 1B of NOA 24-0102.06**Fastener Shear Capacity - Medium-Weight CMU**P_{nv}/Ω: 161 lbs See Table 3 of NOA 24-0102.06**Note:**

- Critical anchor spacing is 16D
- Minimum Anchor Embedment is 1-1/4"
- Minimum Edge Distance is 2-1/4"

Fastener Bending Across Shim Space

L: 0.25 in Maximum Shim Gap

D_{sh}: 0.19 in Shank Diameter of TapconF_{yb}: 100 ksi Yield Strength of Tapcon

Ω: 3.00

$$\frac{F_{yb}}{\Omega} = \frac{M}{S} = \frac{16P_n L}{\pi D^3} \Leftrightarrow P_n = \frac{F_{yb} \pi D^3}{16 \Omega L}$$

Where $M = \frac{P_n L}{2}$ (Guided Bending)P_n/Ω: 539 lbs**Bearing Strength of Masonry Straps - AISI S100**

Size: 1/4 Tapcon Size

D_{sh}: 0.19 in Shank Diameter of Tapcon ScrewF_u: 33 ksi Tensile Strength of Masonry Strap

t: 20 GA

t: 0.0359 in Thickness of Masonry Strap

Ω: 3.00

$$\frac{P_{nv}}{\Omega} = 2.7 * t * D * F_u - (EQ. J4.3.1 - 3, AISI S100)$$

P_{nv}/Ω: 203 lbs