

Registry No. 29824 17520 Edinburgh Drive Tampa, FL 33647 (813) 480-3421

EVALUATION REPORT

FLORIDA BUILDING CODE, 8TH EDITION (2023)

Manufacturer:	GCP Applied Techr 20 Moores Road Malvern, PA (617) 498-4303 www.gcpat.com	nologies, Inc.		Issued August 18, 2023	
Manufacturing Plants	s: Bedford Park, IL Evanston, IL Mt. Pleasant, TN Drummondville, Qu	ebec			
Quality Assurance:	Benchmark Holding	s, LLC (QUA9495)			
SCOPE					
Category: Subcategory: Code Edition: Code Sections: Properties:	Roofing Underlayments Florida Building Code, 8th Edition (2023) including High-Velocity Hurricane Zones (HVHZ) 1507.1.1, 1523.1.1, 1523.6.5.2.1 Physical properties				
REFERENCES					
PRI Construction Materia PRI Construction Materia PRI Construction Materia		Report No. 3173292COQ-005B 3150841COQ-003A WRG-017-02-01 WRG-018-02-01 WRG-050-02-02 WRG-141-02-03 WRG-141-02-04	<u>Standard</u> ASTM D 1970 ASTM D 1970 ASTM D 1970 ASTM D 1970 ASTM D 1970 ASTM D 1970 ASTM D 1970	Year 2017a 2017a 2017a 2017a 2017a 2017a 2017a	

PRODUCT DESCRIPTION AND APPLICATION

GRACE ICE & WATER SHIELD [®]	Grace Ice & Water Shield [®] is a high density cross laminated polyethylene surfaced self-adhered ASTM D 1970 underlayment for use on steep slope roofs.			
GRACE ICE & WATER SHIELD [®] HT	Grace Ice & Water Shield [®] HT is a high density cross laminated polyethylene surfaced self-adhered ASTM D 1970 underlayment for use on steep slope roofs			
	Deck Type:	In accordance with FBC requirements.		
	Attachment method: Section 1507.1.1 for the manufacturer's installation	Underlayment shall be attached in accordance with non-HVHZ, FBC Section 1518.2 for the HVHZ, a instructions. It is permissible to backnail the underlayments 12-inch within the headlaps (nails shall be installed perpendic deck with the nail heads flush to the top surface underlayment).	nd the nes o.c. cular to	
	Allowable roof coverings:	Permitted to be used with mechanically fastened roof coverings as prescribed in FBC Section 1507.1.1 for th non-HVHZ and FBC Section 1518.2 for the HVHZ.	าย	
GCP12001.5		FL298-R8 Pag	ge 1 of 2	
This evaluation report is provi	ded for State of Florida product	approval under Rule 61G20-3. The manufacturer shall notify	CREEK	

This evaluation report is provided for State of Florida product approval under Rule 61G20-3. The manufacturer shall notify CREEK Technical Services, LLC of any product changes or quality assurance changes throughout the duration for which this report is valid. This evaluation report does not express nor imply warranty, installation, recommended use, or other product attributes that are not specifically addressed herein.




LIMITATIONS

- 1) Fire Classification is not within the scope of this evaluation.
- 2) Wind uplift resistance in not within scope of this evaluation.
- 3) Installation of the evaluated product shall comply with this report, the FBC, and the manufacturer's published application instructions. Where discrepancies exist between these sources, the more restrictive and FBC compliant installation detail shall prevail.
- 4) Deck substrates shall be clean, dry, and free from any irregularities and debris. All fasteners in the deck shall be checked for protrusion and corrected prior to underlayment application.
- 5) Roof slope limitations shall be in accordance with FBC requirements.
- 6) All underlayments shall be installed with the roll length parallel to the eave, starting at the eave, and lapped in success courses installed up the deck in a manner that effectively sheds water from the deck. End laps shall be staggered between courses in accordance with the manufacturer's application instructions.
- 7) The underlayment may be used as described in other current FBC product approval documents.
- 8) Roof coverings shall not be adhered directly to the underlayment. Roof coverings shall be mechanically fastened through the underlayment to the roof deck.
- 9) The underlayment shall not be installed over existing roof coverings.
- 10) Underlayments may be exposed on the roof deck for a maximum duration of 30 days.
- 11) All products listed in this report shall be manufactured under a quality assurance program in compliance with Rule 61G20-3.

COMPLIANCE STATEMENT

The products evaluated herein by Zachary R. Priest, P.E. have demonstrated compliance with the Florida Building Code, 8th Edition (2023) including High-Velocity Hurricane Zones (HVHZ) as evidenced in the referenced documents submitted by the named manufacturer.



This item has been digitally signed and sealed by Zachary R. Priest, PE, on 8/18/2023.

Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

Zachary R. Priest, P.E. Florida Registration No. 74021 Organization No. ANE9641

CERTIFICATION OF INDEPENDENCE

CREEK Technical Services, LLC does not have, nor will it acquire, a financial interest in any company manufacturing or distributing products under this evaluation.

CREEK Technical Services, LLC is not owned, operated, or controlled by any company manufacturing or distributing products under this evaluation.

Zachary R. Priest, P.E. does not have, nor will acquire, a financial interest in any company manufacturing or distributing products under this evaluation.

Zachary R. Priest, P.E. does not have, nor will acquire, a financial interest in any other entity involved in the approval process of the product.

END OF REPORT

GCP12001.5

FL298-R8

Page 2 of 2

This evaluation report is provided for State of Florida product approval under Rule 61G20-3. The manufacturer shall notify CREEK Technical Services, LLC of any product changes or quality assurance changes throughout the duration for which this report is valid. This evaluation report does not express nor imply warranty, installation, recommended use, or other product attributes that are not specifically addressed herein.