WOLTERS ENGINEERING

ENGINEERING, DRAFTING, CONSULTING

15211 97th Road N West Palm Beach, FL 33412 Ph/Fx: (561) 225-1982

PRODUCT EVALUATION

PRODUCT: ARMOUR LOC 0.032" ALUMINUM 1 3/4" SNAPLOCK 18" WIDE

ROOF PANEL – HVHZ (FLPA# 35255.5)

MANUFACTURER: 1ST COAST METAL ROOFING SUPPLY

186 STATE ROAD 207 EAST PALATKA, FL 32131

To all concerned,

The Armour Loc 0.032" Aluminum 1 3/4" Snaplock 18" Wide Roof Panel, manufactured by 1st Coast Metal Roofing Supply, is a non-structural Fluropon painted aluminum roof panel (23 ksi min) that meets the requirements of Sections 1507.4 and 1518.9 of the 7th Edition (2020) Florida Building Code. The panel has been tested per TAS 100, TAS 125, and ASTM E8 by Intertek with results shown in test reports L1965.05-450-44-R1 and L1965.07-450-44-R1, and per TAS 110 by PRI Construction Materials Technologies, with results shown in test reports VLS-004-02-01 and VLS-005-02-01.

Technical Documentation:

- 1. Drawing "1CASL18-HZ" dated 8/1/22, signed and sealed by Scott Wolters, PE.
- 2. Test Reports listed above by Architectural Testing, Inc. signed and sealed by Vinu Abraham, PE, and by PRI Construction Materials Technologies, signed and sealed by Zachary R Priest, PE.
- 3. Supplemental Calculations to support 1CASL18-HZ, signed and sealed by Scott Wolters, PE.

I have reviewed this submittal per the requirements of FAC Product Approval Rule Chapter 61G20-3.005 (4). Based on the limitations listed below and those provided in the documents above, this product meets all the requirements of the 7th Edition (2020) Florida Building Code generally, and chapter 15 specifically, including the HVHZ provisions.

<u>Limitations</u>: This panel is approved for use inside and outside of the HVHZ.

Overall Limitations: Maximum Panel Width: 18" (nominal)

Minimum Rib Height: 1 3/4"

Clip Anchors: 18 Ga. galvanized steel, 3 ½" long

Min. Slope: HVHZ: 2"/12"

Non-HVHZ: ½"/12" (with Lap Sealant)

3"/12" (no Lap Sealant)

	Option #1	Option #2
	Installation	Installation
Max. Design Pressure:	-147.5 psf	-191 psf
Clip Anchor Spacing:	4" From Ends, 16" Max. O.C.	4" From Ends, 8" Max. O.C.
Min Panel Fasteners:	#10x1" Panclip Fasteners	#10x1" Panclip Fasteners
	(2) Per Clip	(2) Per Clip

<u>Fire Barrier:</u> Where required by code, install an approved fire barrier. Refer to a current

fire directory listing for fire ratings of this roofing system assembly as well as the location of the fire barrier within the assembly. (See note #2 below)

Note: Outside of the HVHZ, in areas with windspeeds < 170 mph, 1" round

plastic caps meeting the requirements of FBC Section 1507.1.1.1, may be

used to prevent galvanic reactions.

<u>Underlayment:</u> Minimum ASTM D 226 Type II, installed and anchored per FBC Section

1507.1.1.1 (min).

(or)

Any underlayment with a valid FLPA or Miami-Dade NOA

Note: Outside of the HVHZ, in areas with windspeeds < 170 mph, 1" round

plastic caps meeting the requirements of FBC Section 1507.1.1.1 may be

used to prevent galvanic reactions.

Minimum Substrate: 1/2' (15/32" min) 4-ply CDX Plywood or 3/4" solid wood planks (S.G. = .42

min) nailed to 2x rafters spaced 24" max. on center with 8d ring-shank

nails spaced 6" on center.

Note: The 3/4" wood planking must be installed as a solid deck and must be

nailed or fastened in a manner equal to the deck above, or as specified by

a Florida licensed Architect/Engineer

Other Limitations:

- 1. Roof slope must meet requirements of FBC Sections 1507.4.2 or 1515.2.
- 2. Fire classification is not a part of this evaluation. Refer to a current Approved Roofing Materials Directory for fire ratings of this product.
- 3. Design of substrate is by others and is not a part of this evaluation.
- 4. All panel system perimeters, penetrations, and transitions to be flashed and sealed per the requirements of RAS 133.

Re-Roofing:

The Armour Loc 0.032" Aluminum 1 3/4" Snaplock x 18" Wide Roof Panel may be installed over a single layer of existing asphalt shingles, provide the existing roof meets the requirements of Section 1511 of the Florida Building Code.

If you have any questions or need more information concerning this approval, please contact me.

