

PRODUCT EVALUATION REPORT
Horizon Structural Systems, Inc.
C or PBC Through Fastened Wall Panel over Open Framing
Florida Product Approval Number FL 46813.3

Category: Panel Wall
Sub-Category: Siding

Compliance Method: 61G20-3.005 (1)(D)
NON-HVHZ

Product Manufacturer

Horizon Structural Systems, Inc.
1659 W. State Highway 46
New Braunfels, Texas 78132

Manufacturing Location

Horizon Structural Systems, Inc.
1659 W. State Highway 46
New Braunfels, Texas 78132

Engineer Evaluator


R. Keith Joyce, P.E. Florida 59081

Validator

Dennis L. Johnson, P.E., Florida 54340
Florida C.O.A. 30308

Contents

Evaluation Report Pages 1-5 Dated 07-02-2024



Compliance Statement

The product described in this report has demonstrated compliance with the 2023 (8th Edition) Florida Building Code Sections 1404.5

Product Description

Horizon C or PBC Through Fastened structural panels applied over open framing:

1. PBC 26 Gauge
(0.0170 Sheet Thickness) with a minimum $F_y = 80$ ksi and $F_u = 82$ ksi 10.68 Fastener Spacing
2. PBC 26 Gauge
(0.0170 Sheet Thickness) with a minimum $F_y = 80$ ksi and $F_u = 82$ ksi 5.34 Fastener Spacing
3. PBC 24 Gauge
(0.0228 Sheet Thickness) with a minimum $F_y = 50$ ksi and $F_u = 65$ ksi 10.68 Fastener Spacing
4. PBC 24 Gauge
(0.0228 Sheet Thickness) with a minimum $F_y = 50$ ksi and $F_u = 65$ ksi 5.34 Fastener Spacing
5. PBC 22 Gauge
(0.0272 Sheet Thickness) with a minimum $F_y = 50$ ksi and $F_u = 65$ ksi 10.68 Fastener Spacing
6. PBC 22 Gauge
(0.0272 Sheet Thickness) with a minimum $F_y = 50$ ksi and $F_u = 65$ ksi 5.34 Fastener Spacing

Panel Material Standard

Formed steel in compliance with the 2023 (8th Edition) Florida Building Code Section 1405.2 with optional painted finish.

Panel Fastener

Corrosion Resistant #12 – 14 HWH SD as indicated in the **Load Tables** of this Evaluation Report

Substrate Description

Minimum 16 gauge (0.0596 steel thickness) open framing.

Framing must be designed in accordance with the 2023 (8th Edition) Florida Building Code

Quality Assurance Entity

The manufacturer has established compliance of products in accordance with the 2023 (8th Edition) Florida Building Code as relates to Rule 61G20-3.005(3) for manufacturing under a quality assurance program audited by an approved quality assurance entity.

Insulation

Manufacturer's approved products (optional)

Fire Classification

Fire Classification is outside the scope of this evaluation


Shear Diaphragm

Shear Diaphragm is outside the scope of this evaluation

Design Procedure

Based on dimensions of the structure, appropriate wind loads are determined using chapter 16 of the 2023 (8th Edition) Florida Building Code for component loading of roof cladding. These component wind loads are compared to the allowable load listed in the **Load Tables** of this evaluation report. The design professional shall select appropriate fastener pattern and panel gauge to reference in the construction documents for proper installation. Design of support framing must be in compliance with the 2023 (8th Edition) Florida Building Code.

C or PBC Panel Diagram



Notes:

1. Fastener Pattern 10.68" is to be used at the ends of all panels
2. Fastener Pattern 10.68" and 5.34" are to be used at the intermediate supports as indicated in the span load tables to achieve the required uplift load capacity.

Horizon (PBC)

Horizon (PBC) Panel				Section Properties					
Panel Gauge	Fy	Fu	Weight	Negative Bending			Positive Bending		
	ksi	Ksi	Psf	I _{xe}	S _{xe}	Maxo	I _{xe}	S _{xe}	Maxo
				In ⁴	In ³	Kip-in	In ⁴	In ³	Kip-in
26	60*	61.5*	0.92	0.0255	0.0318	1.699	0.0255	0.0373	1.669
24	50	60	1.24	0.0356	0.0511	1.980	0.0356	0.0580	1.980
22	50	60	1.48	0.0413	0.0665	2.350	0.0433	0.0730	2.350

*= Fy is 80 ksi, Fu is 82 ksi reduced to Fy = 60 ksi and Fu = 61.5 ksi in accordance with the 2016 North American Specification for Cold-Formed Steel Structural Members with Supplement 2 (2020) Section A2.3.2.

Notes:

1. All calculations for section properties are calculated in accordance with the 2016 edition of the North American Specification for Cold-Formed Members with Supplement 2 (2020).
2. I_{xe} is for deflection calculations.
3. S_{xe} is for bending calculations.
4. Maxo is for allowable bending moment calculations.
5. All values are for one foot of panel from major rib to major rib.

Horizon Structural Systems

PRODUCT INFORMATION

PBC PANEL

26 gauge (Fy = 60 ksi) #12-14 Fasteners on 10.68" centers for attachment to all supporting members (16 gauge supporting members minimum)										
SPAN TYPE	LOAD TYPE	SPAN IN FEET								
		1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0
Single	Negative Wind Load	575.8	287.9	136.4	76.7	47.5	27.5	17.3	11.6	8.2
	Live Load/Deflection	886.0	301.5	134.0	75.4	47.5	27.5	17.3	11.6	8.2
2-Span	Negative Wind Load	230.3	115.2	76.8	57.6	39.4	27.4	20.1	15.4	12.2
	Live Load/Deflection	907.8	244.7	110.5	62.5	40.1	27.9	20.5	15.7	12.4
3-Span	Negative Wind Load	261.7	130.8	87.2	65.4	49.1	34.2	25.1	19.3	15.2
	Live Load/Deflection	1090.8	302.3	137.3	77.8	50.0	34.8	25.6	19.6	15.4

26 gauge (Fy = 60 ksi) #12-14 Fasteners on 5.34" centers for attachment to all supporting members (16 gauge supporting members minimum)*										
SPAN TYPE	LOAD TYPE	SPAN IN FEET								
		1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0
Single	Negative Wind Load	1151.5	306.9	136.4	76.7	47.5	27.5	17.3	11.6	8.2
	Live Load/Deflection	886.0	301.5	134.0	75.4	47.5	27.5	17.3	11.6	8.2
2-Span	Negative Wind Load	460.6	230.3	108.5	61.4	39.4	27.4	20.1	15.4	12.2
	Live Load/Deflection	907.8	244.7	110.5	62.5	40.1	27.9	20.5	15.7	12.4
3-Span	Negative Wind Load	523.4	261.7	135.0	76.5	49.1	34.2	25.1	19.3	15.2
	Live Load/Deflection	1090.8	302.3	137.3	77.8	50.0	34.8	25.6	19.6	15.4

** = Fastener Diameter shall be 1/2" Minimum

Horizon Structural Systems

PRODUCT INFORMATION

PBC PANEL

24 gauge (Fy = 50 ksi) #12-14 Fasteners on 10.68" centers for attachment to all supporting members (16 gauge supporting members minimum)**										
SPAN TYPE	LOAD TYPE	SPAN IN FEET								
		1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0
Single	Negative Wind Load	575.8	287.9	146.5	82.4	52.7	36.6	26.9	20.6	16.3
	Positive Load Wind/Deflection	1315.1	329.6	146.5	82.4	52.7	36.6	24.2	16.2	11.4
2-Span	Negative Wind Load	230.3	115.2	76.8	57.6	46.1	32.5	23.9	18.3	14.5
	Positive Load Wind/Deflection	1048.5	284.5	128.6	72.8	46.7	32.5	23.9	18.3	14.5
3-Span	Negative Wind Load	261.7	130.8	87.2	65.4	52.3	40.5	29.8	22.9	18.1
	Positive Load Wind/Deflection	1256.1	351.1	159.8	90.6	58.2	40.5	29.8	22.9	18.1

24 gauge (Fy = 50 ksi) #12-14 Fasteners on 5.34" centers for attachment to all supporting members (16 gauge supporting members minimum)**										
SPAN TYPE	LOAD TYPE	SPAN IN FEET								
		1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0
Single	Negative Wind Load	1151.5	329.6	146.5	82.4	52.7	36.6	26.9	20.6	16.3
	Live Load/Deflection	1315.1	329.6	146.5	82.4	52.7	36.6	24.2	16.2	11.4
2-Span	Negative Wind Load	460.6	230.3	128.6	72.8	46.7	32.5	23.9	18.3	14.5
	Live Load/Deflection	1048.5	284.5	128.6	72.8	46.7	32.5	23.9	18.3	14.5
3-Span	Negative Wind Load	523.4	261.7	159.8	90.6	58.2	40.5	29.8	22.9	18.1
	Live Load/Deflection	1256.1	351.1	159.8	90.6	58.2	40.5	29.8	22.9	18.1

** = Fastener Washer Diameter shall be 1/2" Minimum

Horizon Structural Systems

PRODUCT INFORMATION

PBC PANEL

22 gauge (Fy = 50 ksi) #12-14 Fasteners on 10.68" centers for attachment to all supporting members (16 gauge supporting members minimum)**										
SPAN TYPE	LOAD TYPE	SPAN IN FEET								
		1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0
Single	Negative Wind Load	575.8	287.9	173.9	97.8	62.6	43.5	28.0	18.8	13.2
	Live Load/Deflection	1565.5	391.4	173.9	97.8	62.6	43.5	28.0	18.8	13.2
2-Span	Negative Wind Load	230.3	115.2	76.8	57.6	46.1	38.4	28.4	21.7	17.2
	Live Load/Deflection	1236.0	337.1	152.5	86.4	55.4	38.6	28.4	21.7	17.2
3-Span	Negative Wind Load	261.7	130.8	87.2	65.4	52.3	43.6	35.4	27.1	21.5
	Live Load/Deflection	1477.3	415.6	189.5	107.6	69.1	48.1	35.4	27.1	21.5

22 gauge (Fy = 50 ksi) #12-14 Fasteners on 5.34" centers for attachment to all supporting members (16 gauge supporting members minimum)**										
SPAN TYPE	LOAD TYPE	SPAN IN FEET								
		1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0
Single	Negative Wind Load	1151.5	391.4	173.9	97.8	62.6	43.5	28.0	18.8	13.2
	Live Load/Deflection	1565.5	391.4	173.9	97.8	62.6	43.5	28.0	18.8	13.2
2-Span	Negative Wind Load	460.6	230.3	152.5	86.4	55.4	38.6	28.4	21.7	17.2
	Live Load/Deflection	1236.0	337.1	152.5	86.4	55.4	38.6	28.4	21.7	17.2
3-Span	Negative Wind Load	523.4	261.7	174.5	107.6	69.1	48.1	35.4	27.1	21.5
	Live Load/Deflection	1477.3	415.6	189.5	107.6	69.1	48.1	35.4	27.1	21.5

** = Fastener Washer Diameter shall be 1/2" Minimum

Notes:

1. Allowable loads are based on uniform span length and uniformly distributed load.
2. Allowable gravity load is limited by bending, shear or deflection.
3. Allowable gravity loads are computed for a maximum total load deflection of L/60.
4. Weight of the panel must be included with gravity load combinations as appropriate.
5. This material is subject to change without notice.
6. This material has been developed in accordance with the 2016 North American Specification for Cold-Formed Structural Steel Members with Supplement 2 (2020).

The engineering data contained herein is for the express use of the customers of Horizon Structural Systems Inc. and qualified design professionals.